

| HOPPER | |
|------------|---|
| Width | 1.83m (6') |
| Length | 3.15m (10') |
| Max volume | 4.8m ³ (6.3yd ³) |



| FEEDER BELT | |
|-------------|----------------|
| Width | 1050mm (42") |
| Type | Plain belt |
| Control | Variable speed |

| MAIN BELT | |
|----------------------|----------------|
| Width | 1050mm (42") |
| Type | Plain belt |
| Control | Variable speed |
| Min Discharge height | 2.3m (7' 6") |
| Max Discharge height | 3.90m (12' 8") |

| VIBRATING GRID | | |
|----------------|----------------|--------------|
| Length | 3.70m (12' 1") | |
| Width | 2m (6' 7") | |
| Screen decks | Bofor Bars | Finger Tines |
| | Punch Plate | Mesh |

| TRACKS | |
|--------|-------|
| Width | 400mm |
| Speed | 1km/h |

| POWERPACK | |
|----------------|-------------------------------|
| Diesel tank | 180L (39 gallon/47 US gallon) |
| Hydraulic tank | 375L (82 gallon/99 US gallon) |

OPTIONS

1. Dust cover over main belt
2. Radio remote control
3. Overband Magnet
4. Tier 3 - T.Deutz 2011 - 49Kw or JCB444 DieselMAX - 63Kw - ROW
 Tier 4i/Stage 3b - JCB EcoMAX 68Kw - EU (Until Dec 2019)
 Tier 4F - JCB444 EcoMAX 55kW - Optional CAT 3.4 T4F - USA
 Stage V - T.Deutz 2.9L4 - 50Kw - EU

PERFORMANCE

| | |
|---------------|---------------|
| Max feed size | 500mm |
| Capacity | up to 600 tph |

WORKING DIMENSIONS

| | |
|--------|-----------------|
| Length | 12.30m (40' 4") |
| Width | 2.56m (8' 4") |
| Height | 4.05m (13' 3") |

TRANSPORT DIMENSIONS

| | |
|--------|-----------------|
| Length | 10.80m (35' 6") |
| Width | 2.30m (7' 5") |
| Height | 3.10m (10' 1") |

GENERAL

| | | | |
|--------|-----------|-----------|-----------|
| Weight | 20,000 kg | 22 US TON | 44000 lbs |
|--------|-----------|-----------|-----------|



Copyright 2014 by Anaconda Equipment International. All rights reserved
 This document or any part thereof must not be reproduced without the permission of Anaconda