



Kubota

TURF EQUIPMENT

KUBOTA TURF LINE-UP 2022



ZD1511LF/ZD1511RL/ZD1511RLF
DIESEL



ZD1211/ZD1211R/ZD1211RL
DIESEL



ZD1011/ZD1021
DIESEL



ZG327PA/ZG327RPA
GASOLINE



ZG222A/ZG227A/ZG227LA
GASOLINE



Z781KWiTW
GASOLINE (EFI engine)

NEW



Z751KWi/Z781KWi/Z781KWTi
GASOLINE (EFI engines)



Z724XKW/Z726XKW
Z723KH/Z724KH/Z725KH
GASOLINE



Z412KW/Z422KW/Z422KWT
Z411KW/Z421KW/Z421KWT
GASOLINE



Z231KW/Z231BR/Z231KH
Z251BR/Z251KH
GASOLINE



F2690E/F2690/F3990
DIESEL



GR2020G/GR2120
GASOLINE DIESEL



T2090BR/T2290KW/T2290KWT
GASOLINE



SZ19/SZ22/SZ26
GASOLINE GASOLINE (EFI engine)



WHF14/WHF15/WHF18
GASOLINE

NEW



WG6/WGC6
GASOLINE



www.kubotausa.com

For Earth, For Life
Kubota

Call 800-848-4211 or visit us online at www.kubotausa.com



KUBOTA CONSTRUCTION EQUIPMENT

LINE-UP 2021



KX Series



KX008-3

Digging Depth: 5'9" (1,715 mm)
Digging Radius at Ground Level: 9'11" (3,025 mm)
Operating Weight: 2,190 lbs. (995 kg)
Horsepower: 10.3 (7.7 kW) / 2,050 rpm



KX018-4

Digging Depth: 7'9.7" (2,380 mm)
Digging Radius at Ground Level: 12'8" (3,860 mm)
Operating Weight: CANOPY/CAB
3,737 lbs. (1,695 kg) / 3,957 lbs. (1,795 kg)
Horsepower: 15.3 (11.4 kW) / 2,300 rpm



KX018-4

Digging Depth: 7'9.7" (2,380 mm)
Digging Radius at Ground Level: 12'8" (3,860 mm)
Operating Weight: CANOPY/CAB
3,737 lbs. (1,695 kg) / 3,957 lbs. (1,795 kg)
Horsepower: 15.3 (11.4 kW) / 2,300 rpm



KX033-4

Digging Depth: 10'6" (3,210 mm)
Digging Radius at Ground Level: 16'10" (5,120 mm)
Operating Weight: CANOPY/CAB
7,420 lbs. (3,365 kg) / 7,742 lbs. (3,511 kg)
Horsepower: 24.8 (18.5 kW) / 2,200 rpm



KX040-4

Digging Depth: 11'2.7" (3,420 mm)
Digging Radius at Ground Level: 17'9" (5,410 mm)
Operating Weight: CANOPY/CAB
9,195 lbs. (4,170 kg) / 9,500 lbs. (4,310 kg)
Horsepower: 40.4 (30.1 kW) / 2,200 rpm



KX057-5

Digging Depth: 12'9" (3,875 mm)
Digging Radius at Ground Level: 20'1" (6,125 mm)
Operating Weight: CANOPY/CAB
12,346 lbs. (5,600 kg) / 12,577 lbs. (5,705 kg)
Horsepower: 47.6 (35.5 kW) / 2,200 rpm

U Series



U17

Digging Depth: 7'7" (2,310 mm)
Digging Radius at Ground Level: 12'7" (3,840 mm)
Operating Weight: 3,693 lbs. (1,675 kg)
Horsepower: 16.1 (12.0 kW) / 2,300 rpm



U27-4

Digging Depth: 9'5" (2,870 mm)
Digging Radius at Ground Level: 15'4" (4,680 mm)
Operating Weight: CANOPY/CAB
5,688 lbs. (2,580 kg) / 5,908 lbs. (2,680 kg)
Horsepower: 20.8 (15.6 kW) / 2,400 rpm



U35-4

Digging Depth: 9'8.3" (2,970 mm)
Digging Radius at Ground Level: 16'11.3" (5,165 mm)
Operating Weight: CANOPY/CAB
8,488 lbs. (3,850 kg) / 8,810 lbs. (3,996 kg)
Horsepower: 24.8 (18.5 kW) / 2,200 rpm



U48-5

Digging Depth: 10'8" (3,255 mm)
Digging Radius at Ground Level: 18'4" (5,585 mm)
Operating Weight: CANOPY/CAB
10,848 lbs. (4,920 kg) / 11,057 lbs. (5,015 kg)
Horsepower: 40.4 (30.1 kW) / 2,200 rpm



U55-5

Digging Depth: 11'11" (3,630 mm)
Digging Radius at Ground Level: 19'7" (5,965 mm)
Operating Weight: CANOPY/CAB
12,247 lbs. (5,555 kg) / 12,456 lbs. (5,650 kg)
Horsepower: 47.6 (35.5 kW) / 2,200 rpm



KX080-4S2

Digging Depth: 15'1.1" (4,600 mm)
Digging Radius at Ground Level: 23'6.3" (7,170 mm)
Operating Weight: RUBBER/STEEL
18,596 lbs. (8,435 kg) / 18,706 lbs. (8,485 kg)
Horsepower: 66.6 (49.7 kW) / 2,000 rpm

R Series



R430

Operating Weight: CANOPY/CAB
7,758 lbs. (3,519 kg) / 8,232 lbs. (3,734 kg)
Bucket Capacity: 0.5 cu.yd. (0.38 m³)
Horsepower: 47.6 (35.5 kW) / 2,600 rpm



R540

Operating Weight: CANOPY/CAB
9,888 lbs. (4,485 kg) / 10,285 lbs. (4,665 kg)
Bucket Capacity: 0.85 cu.yd. (0.65 m³)
Horsepower: 50.9 (38.0 kW) / 2,400 rpm



R640

Operating Weight: CANOPY/CAB
11,177 lbs. (5,070 kg) / 11,563 lbs. (5,245 kg)
Bucket Capacity: 0.94 cu.yd. (0.72 m³)
Horsepower: 64.3 (48.0 kW) / 2,400 rpm

SVL Series



SVL65-2

Rated Operating Capacity @ 35% of Tipping Load:
2,100 lbs. (953 kg)
Operating Weight: Open CAB 8,069 lbs. (3,660 kg)
Closed CAB 8,565 lbs. (3,885 kg)
Engine Horsepower: 68.4 (51.0 kW) / 2,600 rpm



SVL75-2

Rated Operating Capacity @ 35% of Tipping Load:
2,300 lbs. (1,043 kg)
Operating Weight: Open CAB 9,039 lbs. (4,100 kg)
Closed CAB 9,314 lbs. (4,225 kg)
Engine Horsepower: 74.3 (55.4 kW) / 2,400 rpm



SVL97-2

Rated Operating Capacity @ 35% of Tipping Load:
3,200 lbs. (1,451 kg)
Operating Weight: Open CAB 11,299 lbs. (5,125 kg)
Closed CAB 11,574 lbs. (5,250 kg)
Engine Horsepower: 96.4 (71.9 kW) / 2,400 rpm

SSV Series



SSV65

Rated Operating Capacity @ 50% of Tipping Load:
1,950 lbs. (885 kg)
Operating Weight: Open CAB 6,790 lbs. (3,080 kg)
Closed CAB 7,055 lbs. (3,200 kg)
Engine Horsepower: 64.0 (47.7 kW) / 2,700 rpm



SSV75

Rated Operating Capacity @ 50% of Tipping Load:
2,690 lbs. (1,220 kg)
Operating Weight: Open CAB 8,157 lbs. (3,700 kg)
Closed CAB 8,422 lbs. (3,820 kg)
Engine Horsepower: 74.3 (55.4 kW) / 2,600 rpm



KUBOTA TRACTOR CORPORATION
Cub. Model: SVL65-2, SVL75-2, SVL97-2, SSV65, SSV75

www.kubotaUSA.com

For Earth, For Life
Kubota