

# STIHL BLOWERS & SHREDDER VACS

	Power Source Type	Displacement (cc/cu. in.)	Engine Power (kW/bhp)	Voltage (V)	Weight (lbs.)	Fuel Capacity (oz.)	Sound Pressure Level - dB(A)**	Maximum Air Velocity (mph)**	Air Volume at Nozzle (cfm)**	Blowing Force / Newtons**	Round Nozzle	Flat Nozzle	Curved Round Nozzle	Anti-Vibration System	STIHL Easy2Start™ (E)	STIHL ElastoStart™	Low-Noise Sound Damper (L)	Hip Belt	Lightweight Version (X)	Adjustable Tube	Toolless Adjustable Handle	Caring for Nature	Made in America°	
<b>WEEKLY USE AROUND BEDS AND DRIVEWAYS</b>																								
<b>BGA 45</b>		—	—	18	4.4	—	60	98	247	5	●	—	—	—	—	—	—	—	—	—	—	—		—
<b>BG 50</b>		27.2/1.66	0.7/0.9	—	7.9	14.5	70	159	412	13	●	—	—	—	—	—	—	—	—	—	—	—		
<b>BG 56 C-E</b>		27.2/1.66	0.7/0.9	—	9.3	18.3	70	159	412	13	●	—	—	—	●	—	—	—	—	—	—	—		
<b>SH 56 C-E</b>		27.2/1.66	0.7/0.9	—	11.5	18.3	70	159	412	13	●	○	—	—	●	—	—	—	—	●	—	—		
<b>SHA 56</b>		—	—	36	S:9.3 B:7.1	—	62	125	328	8	●	○	—	—	—	—	—	—	—	—	●	—	—	
<b>BGA 57</b>		—	—	36	5.1	—	59	123	365	9	●	○	—	—	—	—	—	—	—	—	●	—		
<b>NEW! BGA 60</b>		—	—	36	5.0	—	56	154	459	13/15 <sup>1</sup>	●	—	—	—	—	—	—	—	—	—	●	—		
<b>BGE 61</b>		—	—	120	6.8	—	64	148	285	9	—	●	—	—	—	—	—	—	—	●	—	—		
<b>BGE 71</b>		—	—	120	6.8	—	58/64	L:119/H:148	L:232/H:285	L:6/H:9	—	●	—	—	—	—	—	—	—	●	—	—		
<b>LARGER AREAS, NUMEROUS TREES</b>																								
<b>BG 66 L</b>		27.2/1.66	0.6/0.8	—	9.7	18.3	65	139	371	10	●	—	—	—	—	●	—	—	—	●	—	—		
<b>BGA 86</b>		—	—	36	6.2	—	58	154	459	15	●	○	—	—	—	—	—	—	—	●	—	●		
<b>BG 86</b>		27.2/1.66	0.8/1.07	—	9.7	14.9	70	F:190/R:154	F:365/R:444	15	●	●	—	●	—	—	—	—	—	—	—	●		
<b>BG 86 C-E</b>		27.2/1.66	0.8/1.07	—	9.9	14.9	70	F:190/R:154	F:365/R:444	15	●	●	—	●	●	—	—	—	—	—	●	—		
<b>SH 86 C-E</b>		27.2/1.66	0.8/1.07	—	12.3	14.9	70	170	444	15	●	—	—	●	●	—	—	—	—	—	●	—		
<b>BGA 100</b>		—	—	36	5.5	—	56 <sup>1</sup>	168 <sup>1</sup>	494 <sup>1</sup>	17 <sup>1</sup>	●	○	—	—	—	—	—	—	—	—	●	—		
<b>BGA 200</b>		—	—	36	7.1	—	59 <sup>1</sup>	188 <sup>1</sup>	553 <sup>1</sup>	21 <sup>1</sup>	●	○	—	—	—	—	—	—	—	—	●	—		
<b>NEW! BGA 300</b>		—	—	36	16.5	—	59 <sup>1</sup>	192 <sup>2</sup>	571 <sup>2</sup>	26 <sup>2</sup>	●	○	—	—	—	—	—	—	—	●	—			
<b>BR 200</b>		27.2/1.66	0.8/1.07	—	12.6	35.5	70	150	400	12	●	—	○	●	—	—	—	—	—	●	—	—		
<b>BR 350</b>		63.3/3.86	2.1/2.8	—	22.0	57.5	74	201	436	17	●	○	—	●	—	—	—	—	○	—	●	—		
<b>PROFESSIONAL JOBS, EXTENDED BLOWING TIMES</b>																								
<b>BR 430</b>		63.3/3.86	2.9/3.9	—	22.3	57.5	76	219	500	26	●	○	○	●	—	●	—	—	○	—	●	—	—	
<b>BR 450</b>		63.3/3.86	2.9/3.9	—	23.4	57.5	77	219	642	28	●	—	○	●	—	—	—	—	○	—	●	●		
<b>BR 500</b>		64.8/3.95	2.0/2.7	—	22.3	47.3	65	207	544	22	●	—	○	●	—	—	●	●	○	—	●	●		
<b>BR 600</b>		64.8/3.95	2.8/3.8	—	21.6	47.3	75	238	677	32	●	○	○	●	—	—	—	—	○	—	●	—		
<b>BR 700</b>		64.8/3.95	2.8/3.8	—	23.4	47.3	75	197	912	35	●	○	○	●	—	—	—	—	○	—	●	●		
<b>BR 700 X</b>		64.8/3.95	2.8/3.8	—	23.0	47.3	75	193	901	34	●	—	—	●	—	—	—	—	○	—	●	●		
<b>BR 800 C-E MAGNUM®</b>		79.9/4.9	3.2/4.4	—	25.8	67.6	78	239	912	41	●	○	○	●	●	—	—	—	●	—	●	●		
<b>BR 800 X MAGNUM®</b>		79.9/4.9	3.2/4.4	—	23.1	67.6	78	239	912	41	●	—	—	●	—	—	—	—	●	●	●	●		

● Standard    ○ Optional    — Not Applicable  
 L = Low    H = High    F = Flat tube    R = Round tube

\*Dry weight.  
 \*\*As measured per ANSI B175.2 standard (gasoline-powered blowers only).  
 \*\*\*Newton is the force needed to accelerate 1 kg of mass at the rate of 1 m/sec<sup>2</sup>.  
<sup>1</sup>Measurements in Boost mode. <sup>2</sup>Boost mode with AR 3000 L.

Note: Specifications are as of Oct. 1, 2022. For most recent updates, visit [STIHLusa.com](http://STIHLusa.com). Models and specifications are subject to change without notice. Manufacturer reserves the right to change appearance, function and components of any STIHL product without prior notice or liability.

<sup>°</sup>Made in America of U.S. and global materials. Batteries and chargers sourced internationally.

**STIHL**