



HOPPER

Width	1.47m (4' 8")
Length	3.72m (12' 2")
Max volume	4m³ (5.2yd³)
<i>without extensions</i>	

FEEDER BELT

Width	900mm (35")
Type	Plain belt
Control	Variable speed

DRUM

Length	5.15m (16' 9")
Diameter	1.37m (4' 5")
Angle	0-5°

COLLECTION & TRANSFER BELT

Collection Width	900mm (35")
Transfer Width	650mm (25")
Control	Variable speed

FINES BELT

Width	800mm (31")
Discharge Height	2.72m (8' 9")
Control	Variable speed

OVERSIZE (TAIL) BELT

Width	900mm (35")
Discharge Height	2.47m (8' 1")
Control	Variable speed

TRACKS

Width	300mm
Speed	1km/h

POWERPACK

Diesel tank	260L (57 gallon/68 US gallon)
Hydraulic tank	345L (75 gallon/91 US gallon)

OPTIONS

1. Radio remote tipping grid
2. Punch plate screens
3. Radio remote control
4. Wheel Version
5. Tier 3 - JCB444 DieselMAX - 63Kw - ROW
 Tier 4i/Stage 3b - JCB EcoMAX 68Kw - EU (Until Dec 2019)
 Tier 4F - JCB444 EcoMAX 55kW - Optional CAT 3.4 T4F - USA
 Stage V - JCB - EU

PERFORMANCE

Max feed size	300mm
Max screen size	60mm
Capacity	up to 150 tph

WORKING DIMENSIONS *Without Grid*

Length	13.37M (43' 8")
Width	6.37M (20' 9")
Height	3.15M (10' 3")

TRANSPORT DIMENSIONS *Without Grid*

Length	11.69M (38' 3")
Width Max	2.42M (7' 9")
Width Min	2.28M (7' 5")
Height Max	2.73M (8' 9")
Height Min	2.54M (8' 3")

GENERAL

Weight	14,500 kg	16 US TON	32000 lbs
--------	-----------	-----------	-----------



Copyright 2014 by Anaconda Equipment International. All rights reserved
 This document or any part thereof must not be reproduced without the permission of Anaconda