

HOPPER

Width	2.0m (6' 6")
Length	3.7m (12' 2")
Max volume	9.6m ³ (12.6yd ³)

with extensions

FEEDER BELT

Width	1m (40")
Feed Height	2.85m
Control	Yes

DRUM

Length	5.50m (18')
Diameter	2.0m (6' 7")
Angle	0-6 °

COLLECTION BELT

Width	1050mm (42")
Control	Variable speed

TRANSFER BELT

Width	800mm (32")
Control	Variable speed

FINES BELT

Width	1m (40")
Discharge Height	3.10m @ 30 degrees
Control	Variable speed

OVERSIZE (TAIL) BELT

Width	1m (40")
Discharge Height	3.30m @ 30 degrees
Control	Variable speed

TRACKS

Width	500mm
Speed	1km/h

POWERPACK

Diesel tank	265L (58 gallon/70 US gallon)
Hydraulic tank	370L (81 gallon/97 US gallon)



OPTIONS

1. Tipping Grid
2. Single Vibrating Grid
3. Hopper Extensions
4. Punch Plate Solid Drum
5. Wheel version
6. Tier 3 - CAT 4.4 (74.5Kw) or JCB444 (85kW) DieselMAX - ROW Tier 4i/Stage 3b - JCB444 EcoMAX (93Kw) - EU (Until Dec 2019) Tier 4F - JCB444 EcoMAX (81Kw) - Optional CAT 4.4T4F - USA Stage V - JCB444 EcoMax - EU (From Jan2020)

PERFORMANCE

Max feed size	300mm (12")
Max screen size	75mm (3")
Capacity	up to 200 tph

WORKING DIMENSIONS

Length	13.85m (45' 4")
Width	6.90m (22' 6")
Height	3.74m (12' 3")

TRANSPORT DIMENSIONS

Length	11.35m (37' 2")
Width	3.0m (9' 10")
Height	3.45m (11' 3")

GENERAL

Weight	20,000 kgs		44000 lbs
--------	------------	--	-----------



A McLanahan Company

Copyright 2014 by Anaconda Equipment International. All rights reserved

This document or any part thereof must not be reproduced without the permission of Anaconda